

Get latest firmware version for charge controllers

If you need the latest available firmware for your Ensto Chago charger, find it below.



You can use USB stick based method (see [Update firmware with USB stick](#)) or OCPP FirmwareUpdate request to update the software. You can only go to a newer version, not back to an older version, this is by design.



Note: In case the charger is connected to any back-end, before updating please check with the back-end operator what is the latest approved firmware version that can be used with their back-end.

Gen 1 charger Version	Debian package	Notes	Gen 2 version (charger with new controller) Debian package
5.32.0-18892	firmware_5.32.0-18892.deb	Common improvements. Postponed.	firmware_5.32.0-18892_ICC1324.deb
5.29.4-13558	firmware_5.29.4-13558.deb	Replaces 5.29.3fw which had one update related bug.	
5.29.3-13498	firmware_5.29.3-13498.deb	Fixes connectivity issues.	
5.20.5-13170	firmware_5.20.5-13170.deb	IMPORTANT! Healthy reboot parameter must be set to 20 or less for this firmware version. OCPP Parameter name: DaysScheduledReboots = 20 New webUI, MiFARE Desfire EV2-J secure RFID, new Building Automation Energy Management protocols, local charging scheduler, Autocharge, over and under voltage monitor .	
4.66-6074	firmware_4.66-6074.deb	OCPP JSON re-connection fix, OCPP Master/Slave memory segmentation fault fix, OCPP 1.6 JSON Basic Auth, RFID learning mode.	
4.63-6011	firmware_4.63-6011.deb	EV-Wakeup improvements, IT-Network DLM improvements.	
4.60-5939	firmware_4.60-5939.deb	Wake-up / Polling for DLM	
4.53-5444	firmware_4.53-5444.deb	DLM bug fixes and several other fixes.	
4.21-3390	firmware_4.21-3390.deb	Some bug fixes for the DLM.	
4.20-3337	firmware_4.20-3337.deb	Obsolete not actively supported anymore	
4.02-2222	firmware_4.02-2222.deb	Obsolete not actively supported anymore	
3.35-1440	firmware_3.35-1440.deb	Obsolete not actively supported anymore	

Related articles

- [Configure Advanced Dynamic Load Management](#)
- [Endre CPU hastighet](#)
- [Konfigurere statisk IP adresse for laderen](#)